



STEAMTECH CLEANING SYSTEMS



QUALITY BUILT, INDUSTRIAL GRADE MULTI-PURPOSE SATURATED STEAM GENERATORS WITH WET/DRY VACUUM CAPABILITIES. THESE VERSATILE AND POWERFUL SYSTEMS ARE THE ULTIMATE SOLUTION TO THE TOUGHEST CLEANING AND SANITIZING CHALLENGES IN ANY PLANT.



- Single and three phase models with powerful boiler sizes of 3600, 10800 and 21600 watts
- Pressure up to 10 bar, steam up to 180°C
- Rotationally moulded and stainless bodies for maximum durability
- Continuous run – immediate refill without de-pressurisation
- Chemical injection for detergents or chemicals
- Vacuum for simultaneous removal of debris and moisture
- Versatile toolset allows the Steamtech to be used for a variety of cleaning and maintenance tasks
- Ease of use results in significant labor savings and less downtime
- Low capital costs plus major cost reductions means a shorter payback period on your investment.

STEAMTECH SYSTEMS

Brought to North America by a Strategic Alliance of:



STANDARD TOOLS...

The SteamTech is supplied with a wide range of standard tools in order to tackle any cleaning task within your production facility. The standard toolset consists of a 4 metre steam/vac hose with handgrip, floor tool, steam/vac turbo lance, squeegee attachment and insert, steam scraper and steel wool, plus a complete set of nylon, brass and stainless steel brushes. With these attachments the SteamTech system can be used to clean on many different types of surfaces such as floors, walls, windows, ceilings, metal surfaces, concrete, ceramic tile and grout lines.

3 STANDARD MODELS...

...AND...

...OPTIONAL EXTRAS

Optional tools for the SteamTech units include an 8 metre or 12 metre steam/vac hose, squeegee-brush, brush-brush, carpet tool, carpet insert, stainless steel insert, steam/vac window cleaner, suction nozzle and upholstery nozzle.

For more information:
www.totalvap.com or

TECHNICAL DATA

STEAMTECH	MODEL 4000	MODEL 8000	MODEL 12000
Power Supply	230 V Single Phase 50/60 Hz	480 V Three Phase 50/60 Hz	480 V Three Phase 50/60 Hz
Water Reserve Tank	15 L 3.96 Gal	15 L 3.96 Gal	15 L 3.96 Gal
Detergent Tank	15 L 3.96 Gal	15 L 3.96 Gal	15 L 3.96 Gal
Boiler Output	3600 Watt	7200 Watt	10800 Watt
Steam Temp. *	165°C 329°F	165°C 329°F	165/180°C 329/356°F
Operating Pressure	5 Bar 72 PSI	6 Bar 87 PSI	6 /10Bar 87/145 PSI
Steam Volume/min	97 g 3.4 oz	170 g 6.8 oz	260 g 9.2 oz
Detergent Temp.	90/125°C 194/257°F	90/145°C 194/293°F	90/145°C 194/293°F
Vacuum Drum	14 L 3.70 Gal	14 L 3.70 Gal	14 L 3.70 Gal
Vacuum Power	1200 Watt	1200 Watt	1200 Watt
Vacuum Airflow/hr	200m ³ 262 yd ³	200m ³ 262 yd ³	200m ³ 262 yd ³
Vacuum Depression	2200 mm 86 in	2200 mm 86 in	2200 mm 86 in
Rotationally Molded Body	✓	✓	✓
Stainless Steel Body			
Power Cord	8 m 26.25 ft	8 m 26.25 ft	8 m 26.25 ft
Steam Regulator	✓	✓	✓
12 V Hand Controls	✓	✓	✓
Steam Ready Indicator	✓	✓	✓
Low Water Indicator	✓	✓	✓

* 165°C and 6 Bar with Standard Hose Kit or
 180°C and 10 Bar with High Pressure Lance
 The manufacturer reserves the right to bring any changes or
 modifications to the machines without prior notice

SALES OFFICES

North America:

Tel: 1-800-867-6870
 eMail: info@totalvap.com
 WebSite: www.totalvap.com

STEAMTECH SYSTEM